

We rotationally mold a seamless polyethylene floats, with a consistent wall thickness of 5/16", up to 1/2" upon request. This is to ensure strength and durability against punctures and splits.

- * 1 1/2" drain plug for pump out and ballast.
- * 3/8" T-nuts for attachment of bottom skid plates.
- * 4" flanges to ensure proper attachment to dock framing structure.

NW225

W 24" x L 24" x H 14"
225 lbs of floatation
22 lbs Dry Weight



NW450

W 24" x L 48" x H 14"
450 lbs of floatation
41 lbs Dry Weight



NW550

W 36" x L 39" x H 14"
550 lbs of floatation
45 lbs Dry Weight



**NOSE CONE
NW225
NW450
NW650**



NW650

W 24" x L 72" x H 14"
650 lbs of floatation
60 lbs Dry Weight



NW900

W 24" x L 72" x H 19"
900 lbs of floatation
80 lbs Dry Weight



NW1000

W 46" x L 59" x H 14"
1000 lbs of floatation
84 lbs Dry Weight



**NOSE CONE
NW1000
NW1400**



NW1400

W 46" x L 59" x H 19"
1400 lbs of floatation
92 lbs Dry Weight



NW1800

W 46" x L 59" x H 24"
1800 lbs of floatation
112 lbs Dry Weight



**BOOSTER SADDLE
NW750**



NW2200

W 46" x L 59" x H 29"
2200 lbs of floatation
140 lbs Dry Weight



**NOSE CONE
NW1850**



NW1850 PONTOON FLOAT

W 33" x L 68" x H 30"
1850 lbs of floatation
120 lbs Dry Weight



NW2600

W 48" x L 60" x H 30"
2600 lbs of floatation
141 lbs Dry Weight

