

Rotationally molded seamless polyethylene floats.
Consistent wall thickness of 5/16", or up to 1/2" upon request.

- * 1-1/2" drain plug for pump out and ballast.
- * 3/8" T-nuts casted into floats for attachment of bottom skid plates.
- * 4" flanges with predrilled 5/8" bolt holes to ensure ease of attachment to the dock framing structure.

NW225

W 24" x L 24" x H 14"
225 lbs of floatation
22 lbs Dry Weight



NW450

W 24" x L 48" x H 16"
450 lbs of floatation
39 lbs Dry Weight



NW550

W 36" x L 39" x H 14.5"
550 lbs of floatation
45 lbs Dry Weight



NW650

W 24" x L 70" x H 16"
650 lbs of floatation
60 lbs Dry Weight



NW900

W 24" x L 70" x H 19"
900 lbs of floatation
80 lbs Dry Weight



NW1200

W 24" x L 70" x H 24"
1200 lbs of floatation
92 lbs Dry Weight



NW1000

W 46" x L 59" x H 16"
1000 lbs of floatation
84 lbs Dry Weight



NW1400

W 46" x L 59" x H 19"
1400 lbs of floatation
92 lbs Dry Weight



NW1800

W 46" x L 59" x H 24"
1800 lbs of floatation
126 lbs Dry Weight



NW1850 PONTOON FLOAT

W 34" x L 70" x H 30"
1850 lbs of floatation
120 lbs Dry Weight



NW2600

W 60" x L 48" x H 30"
2600 lbs of floatation
142 lbs Dry Weight



NOSE CONE

NW1000
NW1400



BOOSTER SADDLE

NW750



NOSE CONE

NW225
NW450
NW650



NOSE CONE

NW1850



NOSE CONE

NW2600

